

CUSTOM BOLSTERS



DESCRIPTION

Safety bollard, diameter 35 mm.
Continuous load-bearing structure in extruded aluminum.
Smooth cover in Titanium Dioxide Polymers, thickness 2.5 mm.
Fireproof, anti-pollutant, anti-bacterial, high resistance to impacts, odorless, resistant to atmospheric and chemical agents.
Accessories, supports, curves and rosette covers and under-rosettes in Nylon V0.
Multi-hole wall attachment rosettes in galvanized steel, electrically insulated.
Wall fixing with screws and dowels supplied..

RANGE

Impact resistance 150 kg.

MEASURES

Tailor-made to customer specifications

STANDARD LENGTH

6m bars.

COLORS

S0 White - S1 Ivory - S2 Light Blue - S3 Pastel Green - S4 Light Grey - S5 Charcoal Grey
S6 Yellow - S7 Blue - S8 Dark Green - S9 Silver Grey - S10 Brown - S11 Black - S12 Red
S13 Wild Rose - S14 Salmon

CERTIFICATIONS

ISO 9001:2015 Quality Certification issued by TÜV Italia S.r.l.
Fire reaction class certification B-s2,d0.
Certification attesting the absence of bacterial growth issued by CSI IMQ group.
Declaration of the Quality Office, certifying the non-use of Cadmium and/or heavy metals.
Declaration of the Quality Office, certifying biocompatibility and recyclability.

MPS reserves the right to make any changes deemed necessary to improve the products without prior notice.